



AMERICAN BEARING MFG.CORP.



7.48 Inch | 190 Millimeter x 13.386 Inch | 340
 Millimeter x 4.724 Inch | 120 Millimeter SKF 23238
 CC/C3W33 Spherical Roller Bearings

Bearing No. 23238 CC/C3W33

23238 CC/C3W33 Bearing 2D drawings and 3D CAD
 models

| | |
|---------------------------|--|
| Category | Spherical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 49.044 |
| EAN | 7316576602160 |
| Product Group | B04311 |
| Internal Clearance | C3-Loose |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Steel |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Withdrawal Nut | Not Applicable |
| Inch - Metric | Metric |
| Long Description | 190MM Straight Bore; 340MM Outside Diameter; 120MM Width; C3-Loose Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable |
| Category | Spherical Roller Bearing |



AMERICAN BEARING MFG.CORP.

| | |
|------------------------------|---|
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer URL | http://www.skf.com |
| Weight / LBS | 108.026 |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| D | 13.386 Inch 340 Millimeter |
| d | 7.48 Inch 190 Millimeter |
| B | 4.724 Inch 120 Millimeter |
| bore diameter: | 190 mm |
| maximum rpm: | 1800 RPM |
| outside diameter: | 340 mm |
| operating temperature range: | Maximum of +390 ° F |
| overall width: | 120 mm |
| cage material: | Steel |
| bore type: | Straight |
| bearing material: | Steel |
| outer ring type: | Not Split |
| cage type: | Inner Ring Guided |
| internal clearance: | C3 |
| precision rating: | Not Rated |
| closure type: | Open |
| finish/coating: | Uncoated |
| lubrication hole type: | Lubrication Groove & Hole |
| outer ring width: | 120 mm |
| dynamic load capacity: | 1660 kN |
| fillet radius: | 3 mm |
| static load capacity: | 2400 kN |
| series: | 232 |